

คีย์ คุณสมบัติ

- 3rd generation laser phosphor technology with up to a 30,000hour lifespan
- 5,000 ANSI Lumens offering bright images in any environment
- Up to 300" ultra large screen with lower cost-per-inch
- Compact size and light weight reducing cost of transportation and installation
- Installation flexibility: 1.3x optical zoom, H/V keystone, 360° projection, and portrait mode



สินค้า **รายละเอียด**

The LS740HD belongs to ViewSonic's Luminous Superior series, a lamp-free high-brightness projector lineup designed for commercial and educational spaces. With its adoption of the 3rd generation laser phosphor technology, it delivers 5,000 ANSI Lumens for up to 30,000 hours, ensuring bright and vivid images without lamp replacement. The lamp-free design offers an eco-friendly and costeffective solution, while the projector's lightweight and compact design reduces transportation costs. With up to 300" projection in 1080p Full HD with high native contrast, it is well-suited for boardrooms, lecture halls, and public spaces. This projector features a 1.3x optical zoom, H/V keystone, 4 corner adjustment, 360° projection, and a portrait mode for easy setup and versatile applications.



- 1. Front IR
- 2. Lens 3. Focus Ring
- 4. HDMI x2 5. RS232
- 6. USB-A (5V/1.5A, Service)
- 7. Audio Out
- 9. Zoom Ring 10. Top IR
- 11. Keypad 12. Power Button

SPECIFICATION		
Native Resolution:	1920x1080	
Brightness:	5000 (ANSI Lumens)	
Brightness (Center Lumens):	5500	
Contrast Ratio:	3000000:1	
Display Color:	1.07 Billion Colors	
Light Source Type:	Laser Phosphor	
Light Source Life (hours) with Normal Mode:	20000	
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	
Lens:	F=2.43-2.78, f=16.90-21.61mm	
Projection Offset:	132%+/-10%	
Throw Ratio:	1.13-1.47	
Optical Zoom:	1.3X	
Digital Zoom:	0.8x-2.0x	
Image Size:	30"-300"	
Throw Distance:	0.75-9.76m (100"@2.50m)	
Keystone:	H:+/-30° , V:+/-30°	
Audible Noise (Normal):	30dB	
Audible Noise (Eco):	24dB	
Input Lag:	49.5ms	
Resolution Support:	VGA(640 x 480) to WUXGA RB(1920 x 1200) *RB-Reduced Blanking	
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Horizontal Frequency:	15K-102KHz	
Vertical Scan Rate:	24-120Hz	
INPUT		
HDMI:	2 (HDMI 1.4/ HDCP 1.4)	
OUTPUT		
Audio-out (3.5mm):	1	
Speaker:	15W	
USB Type A (Power):	1 (5V/1.5A)	
CONTROL		
RS232 (DB 9-pin male):	1	
USB Type A (Services):	1 (share with USB A Output)	

Carry Bag:

	OTHERS	
	Power Supply Voltage:	Power adaptor: Input: 100~240V Output: 19.5VDC / 11.79A
	Power Consumption:	Normal: 210W Standby: <0.5W
	Operating Temperature:	0~40°C
	Carton:	Brown
	Net Weight:	3.00kg
	Gross Weight:	4.70kg
	Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm
	Packing Dimensions:	400x280x155mm
	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Hungarian, Norsk, total 23 languages
	User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
	STANDARD ACCESSORY	
	Power Cord:	1
	Remote Control:	1
	QSG:	Yes
	Warranty Card:	Yes (CN Only)
OPTIONAL ACCESSORY		
	Wall/Ceiling Mount:	PJ-WMK-007

PJ-CASE-008